



## Form V-2: Mitigation Measures - Range of Changes in Damage

**Modeling Organization:** AIR Worldwide  
**Model Name & Version Number:** AIR Hurricane Model for the U.S. v16.0.0 as implemented in Touchstone v4.1.0  
**Model Release Date:** 9/15/2016

INDIVIDUAL MITIGATION MEASURES			PERCENTAGE CHANGES IN DAMAGE ((REFERENCE DAMAGE RATE - MITIGATED DAMAGE RATE) / REFERENCE DAMAGE RATE) * 100									
			FRAME BUILDING					MASONRY BUILDING				
			WINDSPEED (MPH)					WINDSPEED (MPH)				
			60	85	110	135	160	60	85	110	135	160
	REFERENCE BUILDING	-	-	-	-	-	-	-	-	-	-	
ROOF CONFIG URATIO N	BRACED GABLE ENDS	10.1	13.6	13.2	9.9	6.3	9.7	13.5	13.2	9.8	6.1	
	HIP ROOF	14.0	17.5	16.7	12.8	9.0	13.4	17.2	16.5	13.1	8.8	
ROOF COVERING	METAL	-4.5	-2.6	-1.2	-0.5	-0.5	-4.3	-2.5	-1.1	-0.5	-0.5	
	ASTM D7158 CLASS F SHINGLES (150 MPH)	0.6	0.5	0.3	0.1	0.1	0.6	0.5	0.3	0.2	0.1	
	MEMBRANE	0.0	7.6	8.2	0.0	0.0	0.0	8.1	8.4	0.0	0.0	
	NAILING OF DECK	12.8	22.8	24.2	17.8	10.2	12.3	22.2	23.7	18.1	10.0	
ROOF- WALL STRENGTH	CLIPS	1.7	5.1	10.7	11.6	7.6	1.7	5.4	10.8	11.8	7.4	
	STRAPS	2.2	6.5	13.1	14.1	9.8	2.2	6.7	13.2	14.5	9.6	
WALL- FLOOR STRENGTH	TIES OR CLIPS	0.0	0.4	0.6	2.6	7.0	0.0	0.4	0.5	2.6	6.8	
	STRAPS	0.0	0.8	2.2	6.1	12.7	0.0	0.9	2.1	6.1	12.3	
WALL- FOUNDATION STRENGTH	LARGER ANCHORS OR CLOSER SPACING	0.0	0.4	0.6	2.6	7.0	-	-	-	-	-	
	STRAPS	0.0	0.8	2.2	6.1	12.7	-	-	-	-	-	
	VERTICAL REINFORCING	-	-	-	-	-	0.0	1.1	2.2	6.9	15.0	
OPENING PROTECTION	WINDOW SHUTTERS	9.4	13.2	12.5	10.0	8.2	8.8	12.9	12.2	9.7	7.9	
		9.4	13.2	12.5	10.0	8.2	8.8	12.9	12.2	9.7	7.9	
	DOOR AND SKYLIGHT COVERS	1.7	3.7	5.2	5.0	4.4	1.5	4.0	4.9	4.9	4.3	
WINDOW, DOOR, SKYLIGHT STRENGTH	WINDOWS	13.6	19.8	19.3	16.1	13.9	12.7	18.9	18.6	16.1	13.5	
	ENTRY DOORS	1.7	3.7	5.2	5.0	4.4	1.5	4.0	4.9	4.9	4.3	
	GARAGE DOORS	2.6	4.0	3.7	2.1	1.4	2.8	4.7	3.9	2.3	1.4	
	SLIDING GLASS DOORS	-0.3	-0.6	-0.8	-0.7	-0.6	-0.3	-0.7	-0.8	-0.7	-0.6	
	SKYLIGHT	1.7	1.8	1.6	1.0	0.6	1.5	2.0	1.5	1.0	0.6	
MITIGATION MEASURES IN COMBINATION			PERCENTAGE CHANGES IN DAMAGE ((REFERENCE DAMAGE RATE - MITIGATED DAMAGE RATE) / REFERENCE DAMAGE RATE)*100									
			FRAME BUILDING					MASONRY BUILDING				
			WINDSPEED (MPH)					WINDSPEED (MPH)				
			60	85	110	135	160	60	85	110	135	160
BUIL LDI NG	MITIGATED BUILDING	26.1	45.0	50.5	41.5	26.5	24.7	42.9	48.4	40.6	26.1	