

Form V-2: Mitigation Measures - Range of Changes in Damage

Modeling Organization: AIR Worldwide
Model Name & Version Number: AIR Hurricane Model for the U.S. v17.0.0 as implemented in Touchstone v6.1.0
Model Release Date: 9/4/2018

INDIVIDUAL MITIGATION MEASURES		PERCENTAGE CHANGES IN DAMAGE ((REFERENCE DAMAGE RATE - MITIGATED DAMAGE RATE) / REFERENCE DAMAGE RATE) * 100									
		FRAME BUILDING					MASONRY BUILDING				
		WINDSPEED (MPH)					WINDSPEED (MPH)				
		60	85	110	135	160	60	85	110	135	160
	REFERENCE BUILDING	-	-	-	-	-	-	-	-	-	
ROOF CONFIG URATIO N	BRACED GABLE ENDS	10.8	15.0	13.8	9.2	5.1	10.7	14.9	13.8	9.4	6.0
	HIP ROOF	14.8	19.0	17.4	12.4	7.8	14.4	18.7	17.2	12.6	8.5
ROOF COVERING	METAL	6.0	4.9	3.0	1.7	0.3	6.0	4.7	2.9	1.6	0.5
	ASTM D7158 CLASS FT SHINGLES (150 MPH)	10.5	7.7	4.4	2.3	0.6	10.3	7.4	4.2	2.2	1.0
	MEMBRANE	9.8	14.3	11.4	2.2	0.6	9.8	14.5	11.3	2.1	1.0
	NAILING OF DECK	9.4	18.8	21.1	15.7	8.3	9.3	18.6	20.7	16.2	9.0
ROOF- WALL STRENGTH	CLIPS	1.6	5.8	11.0	10.9	6.1	1.8	5.5	10.6	11.0	6.8
	STRAPS	2.1	7.3	13.4	13.4	8.2	2.3	6.9	13.3	13.8	8.9
WALL- FLOOR STRENGTH	TIES OR CLIPS	0.0	0.4	0.6	2.8	6.3	0.0	0.4	0.6	2.7	7.1
	STRAPS	0.0	0.8	2.2	6.1	12.1	0.0	0.8	2.1	6.2	12.6
WALL- FOUNDATION STRENGTH	LARGER ANCHORS OR CLOSER SPACING	0.0	0.4	0.6	2.8	6.3	-	-	-	-	-
	STRAPS	0.0	0.8	2.2	6.1	12.1	-	-	-	-	-
	VERTICAL REINFORCING	-	-	-	-	-	0.1	1.1	2.2	7.0	15.4
OPENING PROTECTION	WINDOW SHUTTERS	8.5	13.2	12.4	9.1	7.0	8.2	12.9	11.8	9.1	7.7
		8.5	13.2	12.4	9.1	7.0	8.2	12.9	11.8	9.1	7.7
	DOOR AND SKYLIGHT COVERS	1.6	4.0	5.0	4.7	3.3	1.8	3.7	4.6	4.6	4.1
WINDOW, DOOR, SKYLIGHT STRENGTH	WINDOWS	12.1	19.2	18.9	15.3	12.6	11.7	18.5	18.2	15.5	13.0
	ENTRY DOORS	1.6	4.0	5.0	4.7	3.3	1.8	3.7	4.6	4.6	4.1
	GARAGE DOORS	2.4	4.2	3.4	2.1	0.8	2.8	4.4	3.6	2.1	1.4
	SLIDING GLASS DOORS	-0.2	-0.7	-0.8	-0.7	-0.3	-0.3	-0.6	-0.7	-0.7	-0.6
	SKYLIGHT	1.3	1.6	1.4	1.0	0.3	1.4	1.6	1.3	0.9	0.6
MITIGATION MEASURES IN COMBINATION		PERCENTAGE CHANGES IN DAMAGE ((REFERENCE DAMAGE RATE - MITIGATED DAMAGE RATE) / REFERENCE DAMAGE RATE)*100									
		FRAME BUILDING					MASONRY BUILDING				
		WINDSPEED (MPH)					WINDSPEED (MPH)				
		60	85	110	135	160	60	85	110	135	160
BUILDING	MITIGATED BUILDING	34.0	49.6	52.3	41.1	25.3	32.7	47.4	50.3	40.6	25.6